

DEGASSER

Degasser

Degasser, is specially used to remove entrained gas from a liquid, especially from a drilling fluid. Customized degasser is available as per client’s exact requirements.

Vacuum Degasser

JRVD vacuum degasser is a special purpose device for the treatment of gas-cut drilling fluid, specially applied to match up with various mud purification systems. During the operation of gas free mud, VQ vacuum degasser also can be used as a heavy-power agitator. VQ vacuum degasser is available in 5 models as below.



Vacuum Degasser

Technical Specification of Vacuum Degasser

Degasser model	JDVD(N) 240-28	JDVD(N) 270-48	JDVD(N) 300-90	JDVD(N) 360-180	JDVD(N) 360-360
Capacity (m ³ /h)	240	270	300	360	360
Vacuum degree (mmHg)	300-340	400-550	400-550	400-550	400-550
Gear ration	1.67	1.68	1.68	1.72	1.72
Main engine power (Kw)	15	22	30	37	37
Power of vacuum pump (Kw)	2.2Kw-4	2.2Kw-4	4Kw-4	5.5Kw-4	11Kw-4
Speed (r/min)	876	870	880	860	860
Displacement (m ³ /h)	28	48	90	180	360
Mud weight (g.cm ³)	≤2	≤2	≤2.5	≤2.5	≤2.5
Degassing efficiency (%)	≥90	≥90	≥90	≥90	≥90
Weight (kg)	1,200	1,200	1,800	2,500	2,600
Dimension (mm)	1,750x765 x1,510	1,950x1,010 x1,680	2,250x1,235 x1,650	2,400x1,500 x1,900	2,450x1,500 x1,900

Index-2016.10-V1/EN

Copyright © Jereh Global All rights reserved.



Jereh Global Development LLC

Add: No.9 Jereh Road, Laishan District, Yantai, P. R. China

Tel: 0535-6765628 6765630

Fax: 0535-6723171 6723172

Email: petroleum@jereh.com

Http: www.jereh.com