

FISHING CUP

Fishing Cup

Fishing cup is applied mainly for fishing of shivers and fallen objects such as carbide tooth, drill bit and bearing that cannot be carried out of hole by convectional fluid circulation, etc. during drilling process. Fishing cup also possesses important functions to keep hole toe cleaning, increase bit service lift, reduce and prevent drill bit from unexpected damage. Such fishing cup tools are available with all sizes and super performance.



Technical Specifications of Fishing Cup

Fishing Cup Model	Suitable Hole Size (mm)	Thread Connection (in)	I.D. (mm)	O.D. (mm)
JD-FC94	108~117.5	2-3/8 REG	19	94
JD-FC 102	117.5~124	2-7/8 REG	32	102
JD-FC 114	130~149	3-1/2 REG	38	114
JD-FC 127	152.4~162	3-1/2 REG	38	127
JD-FC 140	165~190.5	3-1/2 REG	38	140
JD-FC 168	190.5~216	4-1/2 REG	57	168
JD-FC 178	219~244.5	4-1/2 REG	57	178
JD-FC 190	229~273	4-1/2 REG	57	190
JD-FC 197	235~279.5	5-1/2 REG	70	197
JD-FC 219	244~295	6-5/8 REG	89	219
JD-FC 229	254~305	6-5/8 REG	70	229
JD-FC 245	292~330	6-5/8 REG	89	245
JD-FC 280	330~375	7-5/8 REG	89	280
JD-FC 311	327~375	7-5/8 REG	89	311
JD-FC 327	375~444.5	7-5/8 REG	102	327
JD-FC 340	386~456	7-5/8 REG	102	340

Address:	No.7, Aucma Street, Laishan District, Yantai, Shandong, P.R.China 264003
Tel:	+86-535-6723520 6723201
Fax:	+86-535-6723171 6723272
E-mail:	petroleum@jereh.com; cnjereh@gmail.com
Website:	Http://www.jereh-oilfield.com