

MUD CLEANER

Mud Cleaner

Mud cleaner is essential in handling drilling fluids. Sometimes, mud cleaner is also called desander and desilter assembly for its combined function. Regular mud cleaner is in 5 models as below. Regular models are displayed as below, customized mud cleaner is available as per client's requirements.



Mud Cleaner

Technical Specification of Mud Cleaner

Cleaner Model	JDMC70-4	JDMC70-3	JDMC63-3	JDMC83-2	JDMC60
Treating Capacity (m ³ /h)/(GPM)	120~360 528~1,584	120~270 528~1,180	120~240 528~1,056	60~180 264~792	≤60 ≤264
Desilter cones (in)	4(10~20ea)	4(10~18ea)	4(10~16ea)	4(4~10ea)	4(≤4ea)
Desander cones (in)	12(1~3ea)	10(1~3ea)	10(1~2ea)	10(1~2ea)	8(1ea)
Inlet Diameter(mm)	125~150	125~150	125~150	100~125	75~100
Outlet Diameter (mm)	200	200	200	150~200	125~150
Matching pump(KW)	45~75	45~55	45~55	30~45	15~30
Matching Shaker	GNPS70-4	GNPS70-3	GNZS63-3	GNZS83-2	GNTS60
Shaker Motor (kw)	3.6+2.27	1.3+3.6	2×1.5	2×1.3	0.5
Screen Area (m ²)	2.95	2.2	2.4	1.8	1.0
Remarks	Handling capacity is subject to cone numbers, cone numbers and size can be custom designed as per customer requests. 4" desilter cones =12~15 m ³ /h, 10" desander cone=90m ³ /h				

Address:	No.7, Aucma Street, Laishan District, Yantai, Shandong, P.R.China 264003
Tel:	+86-535-6723520 6723201
Fax:	+86-535-6723171 6723272
E-mail:	petroleum@jereh.com; cnjereh@gmail.com
Website:	Http://www.jereh-oilfield.com