

JET MUD MIXER

Jet Mud Mixer

Jet mud mixer is used to change the fluid or mud density, viscosity by adding and mixing bentonite. Connected by manifold valve, jet mud mixer is composed of sand pump, jet hopper and mixer. Four models of jet mud mixers are available as below. Jereh can provide jet mud mixer as per customer requirements.

Technical Specification of Jet Mud Mixer

Mud Mixer Model	JDMM150-50	JDMM150-40	JDMM150-35	JDMM100
Matching Pump	SB8×6-13(55kw)	SB6×5-13(45kw)	SB5×4-13(30kw)	SB4×3-11(15KW)
Capacity(m ³ /h)/(GPM)	240/1,056	180/792	120/528	60/264
Pressure (Mpa)	0.25~0.40	0.25~0.4	0.25~0.40	0.25~0.40
Inlet (mm)	150	150	150	100
Nozzle caliber (mm)	50	40	35	30
Hopper dimension(mm)	750×750	750×750	600×600	500×500
Burden speed(kg/min)	≤100	≤80	≤60	≤40
Density (g/cm ³)	≤2.8	≤2.4	≤2.0	≤1.5
Viscosity (s)	≤120	≤120	≤80	≤60

Address:	No.7, Aucma Street, Laishan District, Yantai, Shandong, P.R.China 264003
Tel:	+86-535-6723520 6723201
Fax:	+86-535-6723171 6723272
E-mail:	petroleum@jereh.com; cnjereh@gmail.com
Website:	Http://www.jereh-oilfield.com