


REVERSE CIRCULATION JUNK BASKET

Reverse Circulation Junk Basket

Reverse circulation junk basket is used to retrieve all types of small junk objects such as cone, cutter, hand tool and junks from the bottom hole. During drilling operation, Reverse circulation junk basket produces a local reverse circulation of fluid at well core so as to affect a complete recovery of junk in the junk basket. Especially when PDC bit is used, cleaning bottom well by the tool becomes very necessary to ensure the bit with a normal application. The reverse circulation junk basket therefore becomes an essential tool in oil, geology exploration and drilling engineering. Jereh Drilltech offers various junk basket s and also supplies highly customized junk basket as per customer's requirements.



Reverse Circulation Junk Basket

Technical Specifications of Reverse Circulation Junk Basket

Reverse Circulation Junk Basket Model	Suitable Hole Size mm (in.)	Ball Diameter (mm) 改了	Max. Catch Diameter (mm)	Thread Connection API
JD-JB40 (4)	104.8~114.3 (4-1/4~4-1/2)	30	64.5	NC26
JD-JB 44 (4-1/2)	117.5~127 (4-5/8~5)	35	76	NC26
JD-JB 51 (5-1/8)	142.9~152.4 (5-5/8~6)	40	95.5	NC31
JD-JB 56 (5-3/4)	155.6~165 (6-1/8~6-1/2)	40	112	NC38
JD-JB 62 (6-1/4)	168~187.3 (6-5/8~7-3/8)	42	121	NC38
JD-JB 70 (7)	190.5~209.5 (7-1/2~8-1/4)	42	132	4-1/2 REG
JD-JB L77 (7-7/8)	212.7~241.3 (8-3/8~9-1/2)	42	146	NC50
JD-JB 85 (8-5/8)	231.7~260.3 (9-1/8~10-1/4)	50	166	NC50
JD-JB 91 (9-1/8)	244.5~269.9 (9-5/8~10-5/8)	50	182	NC50
JD-JB 95 (9-5/8)	254~275.4 (10~11)	50	192	NC50
JD-JB 101 (10-1/8)	273~295.3 (10-3/4~11-5/8)	50	195.5	NC50
JD-JB 112 (11-1/4)	320.6~346.1 (12-5/8~13-1/4)	55	200	6-5/8 REG
JD-JB 116 (11-3/4)	406.4~444.5 (16~17-1/2)	80	280	6-5/8 REG

Address:	No.7, Aucma Street, Laishan District, Yantai, Shandong, P.R.China 264003
Tel:	+86-535-6723520 6723201
Fax:	+86-535-6723171 6723272
E-mail:	petroleum@jereh.com; cnjereh@gmail.com
Website:	Http://www.jereh-oilfield.com