

## TRAVELLING BLOCK AND HOOK

### Travelling Block and Hook

Travelling Block and Hook are effective devices of drilling rig for lifting. Jereh supplies API 8C certified traveling block and hook with API monogram.

Both integral structure of travelling block with hook, and sole travelling block or sole travelling hook are available.



Travelling Block and Hook

### Technical Specification of Travelling Block and Hook

#### Integral Travelling Block and Hook

Model	JDYG 90	JDYG110	JDYG135	JDYG170	JDYG225	JDYG450
Max. hook load (kN)	900	1,125	1,350	1,700	2,250	4,500
O.D. of sheaves mm(in)	760(30)	760(30)	760(30)	915(36)	1,120(44)	1,524(60)
Number of sheaves	3	4	4	5	5	6
wire line Dia. mm(in)	26(1)	26(1)	29(1-1/8)	29(1-1/8)	32(1-1/4)	38(1-1/2)
Major-hook opening (mm)	110	150	150	180	190	220
Spring travel (mm)	152	150	170	140	180	180
Overall Size (LxWxH) mm	2,350x830x430	2,640x828x625	2,946x836x652	3,402x950x640	3,450x970x660	4,887x1,600x880
Weight (Kg)	2,000	2,310	3,126	4,594	4,732	12,530

#### Travelling Block

Model	JDYC225	JDYC315	JDYC450
Max. hook load (kN)	2,250	3,150	4,500
Sheaves O.D. mm(in)	1,120(44)	1,270(50)	1,524(60)
Number of sheaves	5	6	6
wireline Dia. mm(in)	32(1-1/4)	35(1-3/8)	38(1-1/2)
Major-hook opening (mm)	-	-	-
Spring travel (mm)	-	-	-
Overall Size (LxWxH) (mm)	2,294x1,190x630	2,680x1,350x974	3,075x1,600x800

Weight (Kg)	3,713	6,842	8,135
-------------	-------	-------	-------

**Travelling Hook**

Model	JDDG225	JDDG315	JDDG450
Max. hook load (kN)	2,250	3,150	4,500
Sheaves O.D. mm(in)	-	-	-
Number of sheaves	-	-	-
wireline Dia. mm(in)	-	-	-
Major-hook opening( mm)	190	220	220
Spring travel (mm)	180	200	200
Overall Size (LxWxH) (mm)	2,545x780x750	2,953x890x830	2,950x890x880
Weight (Kg)	2,180	3,410	3,496

Address:	No.7, Aucma Street, Laishan District, Yantai, Shandong, P.R.China 264003
Tel:	+86-535-6723520 6723201
Fax:	+86-535-6723171 6723272
E-mail:	petroleum@jereh.com; cnjereh@gmail.com
Website:	<a href="http://www.jereh-oilfield.com">Http://www.jereh-oilfield.com</a>