

## WASHOVER PIPE

### Washover Pipe

Wash over pipe is one special tool to solve sticking pipe. It has a two-step, double-shouldered thread joint with flush outside and inside diameters.

This buttress-type thread of wash over pipe assures quick make-up and high torsion strength. Size of wash over pipe is available ranging from 3 1/2 to 20 inches in O.D. Contact Jereh Drilltech for such wash over pipe.



Washover Pipe

### Technical Specifications of Washover Pipe

Washover Pipe Model	OD mm (in)	ID (mm)	W.T. (mm)	Min. Well hole (mm)	Max. Wash size (mm)
JD-WP114.3-8.56	Φ114.30 (4 <sup>1</sup> / <sub>2</sub> )	Φ97.18	8.56	Φ120.65	Φ88.90
JD-WP 146.05-9	Φ146.05 (5 <sup>3</sup> / <sub>4</sub> )	Φ128.05	9.00	Φ161.93	Φ120.65
JD-WP 193.68-12.7	Φ193.68 (7 <sup>5</sup> / <sub>8</sub> )	Φ168.28	12.70	Φ212.73	Φ161.93
JD-WP 203.2-9.53	Φ203.20 (8)	Φ184.15	9.53	Φ215.90	Φ177.80
JD-WP 206.38-10.67	Φ206.38 (8 <sup>1</sup> / <sub>8</sub> )	Φ185.04	10.67	Φ215.90	Φ177.80
JD-WP 219.07-12.7	Φ219.07 (8 <sup>5</sup> / <sub>8</sub> )	Φ193.67	12.70	Φ244.48	Φ184.15
JD-WP 228.6-10.8	Φ228.60 (9)	Φ207.01	10.80	Φ250.83	Φ200.03
JD-WP 244.48-11.99	Φ244.48 (9 <sup>5</sup> / <sub>8</sub> )	Φ220.50	11.99	Φ266.70	Φ206.37
JD-WP 273.05-12.57	Φ273.05 (10 <sup>3</sup> / <sub>4</sub> )	Φ247.91	12.57	Φ298.45	Φ234.95
JD-WP 339.72-12.10	Φ339.72 (13 <sup>3</sup> / <sub>8</sub> )	Φ315.52	12.10	Φ365.13	Φ301.62

Address:	No.7, Aucma Street, Laishan District, Yantai, Shandong, P.R.China 264003
Tel:	+86-535-6723520 6723201
Fax:	+86-535-6723171 6723272
E-mail:	petroleum@jereh.com; cnjereh@gmail.com
Website:	Http://www.jereh-oilfield.com