

## TUBING AND COUPLING

### Tubing

Jereh Drilltech supplies various seamless tubing from 1.9”~4-1/2” in grade J55, K55, N80, L80, C95, P110, the length range is R1,R2, and threads in NUE, EUE, PE (Plain End).

The tubing is manufactured and inspected as per API 5CT and API 5B specifications.



Tubing

### Technical Specifications of Tubing

Tubing Size (in)	Nominal Weight (lbs/ft)		O.D.		Wall Thickness		Connector Type					
	Non-upset T&C	Ex-upset T&C	in	mm	in	mm	Steel Grade					
							J-55	L-80	N-80 /Q	C-90	T-95	P-110
2-3/8	4	--	2.375	60.33	0.167	4.24	PN	PN	PN	PN	PN	--
	4.6	4.7	2.375	60.33	0.19	4.83	PNU	PNU	PNU	PNU	PNU	PNU
	5.8	5.95	2.375	60.33	0.254	6.45	--	PNU	PNU	PNU	PNU	PNU
	6.6	--	2.375	60.33	0.295	7.49	--	P	--	P	P	--
	7.35	7.45	2.375	60.33	0.336	8.53	--	PU	--	PU	PU	--
2-7/8	6.4	6.5	2.875	73.03	0.217	5.51	PUN	PNU	PNU	PNU	PNU	PNU
	7.8	7.9	2.875	73.03	0.276	7.01	--	PNU	PNU	PNU	PNU	PNU
	8.6	8.7	2.875	73.03	0.308	7.82	--	PNU	PNU	PNU	PNU	PNU
	9.35	9.45	2.875	73.03	0.34	8.64	--	PU	--	PU	PU	--
	10.5	--	2.875	73.03	0.392	9.96	--	P	--	P	P	--
	11.5	--	2.875	73.03	0.44	11.18	--	P	--	P	P	--
3-1/2	7.7	--	3.5	88.9	0.216	5.49	PN	PN	PN	PN	PN	--
	9.2	9.3	3.5	88.9	0.254	6.45	PNU	PNU	PNU	PNU	PNU	PNU
	10.2	--	3.5	88.9	0.289	7.34	PN	PN	PN	PN	PN	--
	12.7	12.95	3.5	88.9	0.375	9.52	--	PNU	PNU	PNU	PNU	PNU
	14.3	--	3.5	88.9	0.43	10.92	--	P	--	P	P	--
	15.5	--	3.5	88.9	0.476	12.09	--	P	--	P	P	--
	17	--	3.5	88.9	0.53	13.46	--	P	--	P	P	--
4	9.5	--	4	101.6	0.226	5.74	PN	PN	PN	PN	PN	PU
	--	11	4	101.6	0.262	6.65	PU	PU	PU	PU	PU	PU
	13.2	--	4	101.6	0.33	8.38	--	P	--	P	P	--
	16.1	--	4	101.6	0.415	10.54	--	P	--	P	P	--
	18.9	--	4	101.6	0.5	12.7	--	P	--	P	P	--
	22.2	--	4	101.6	0.61	15.49	--	P	--	P	P	--
4-1/2	12.6	12.75	4.5	114.3	0.271	6.88	PNU	PNU	PNU	PNU	PNU	--

15.2	--	4.5	114.3	0.337	8.56	--	P	--	P	P	--
17	--	4.5	114.3	0.38	9.65	--	P	--	P	P	--
18.9	--	4.5	114.3	0.43	10.92	--	P	--	P	P	--
21.5	--	4.5	114.3	0.5	12.7	--	P	--	P	P	--
23.7	--	4.5	114.3	0.56	14.22	--	P	--	P	P	--
26.1	--	4.5	114.3	0.63	16	--	P	--	P	P	--

Note: P—Plain; N—Non upset thread and coupling; U—Upset thread and coupling.

## Tubing Coupling

Couplings are important accessories for tubing and casing pipes. Jereh Drilltech supplies various API 5CT/5B/5L casing and tubing couplings from 1.66" to 13-3/8" in threads: NU, EU, STC, BTC, LTC. The casing and tubing couplings can be made in grade H40, J55, K55, N80, L80, P110 and so on.



### Technical Specifications of Tubing Coupling

Tubing Coupling Size (in)	O.D. (in)	Minimum Length(in)	Weight (lbs)
	Round Thread	Round Thread	Round Thread
2-3/8	2.875	4-1/4	2.82
2-7/8	3.500	5-1/8	5.15
3-1/2	4.250	5-5/8	8.17
4	4.750	5-3/4	9.58
4-1/2	5.200	6-1/8	10.77

Address:	No.7, Aucma Street, Laishan District, Yantai, Shandong, P.R.China 264003
Tel:	+86-535-6723520 6723201
Fax:	+86-535-6723171 6723272
E-mail:	petroleum@jereh.com; cnjereh@gmail.com
Website:	Http://www.jereh-oilfield.com